

## AKH-B 220 S

**Wetting and Dispersing Additive (Solvent Based) Anti Flooding/Floating )**

### Product Data

### Composition Applications

**Applications >  
Recommended for >  
Particularly Recommended:  
Special Feature:**

General wetting and dispersing additive for solvent-borne coatings for stabilizing fillers, organic, inorganic, and carbon black pigments in all kinds of resin systems (specially recommended for epoxy coatings) such as two-pack polyurethane and chlorinated polymer systems, two-pack epoxy resin systems, alkyd/amino resin combinations, nitrocellulose systems, solvent-based primer and base-coat of automotive coatings (saturated polyester systems).

Prevent the flooding/floating of titanium dioxide in combination with colored pigments.

**Physical Form:** Clear yellow liquid

**Active Content:** 52%

**Non-volatile matter (10 min., 150 °C):** 52%

**Physical Form:** Clear yellow liquid

High molecular weight polyester

**Based on  
Total formulation weight:** 0.2-0.5%

**Titanium dioxide:** 2%

**Inorganic pigments:** 3-5%

**Organic pigments:** 4-6%

Coatings > Solvent based systems  
> Epoxy resin systems

Prevents flooding/floating



021-88864998  
021-88865279  
0912-5248514



[www.asanchem.com](http://www.asanchem.com)



[@Asankimia](https://www.instagram.com/Asankimia)  
[asan.chem](https://www.facebook.com/asan.chem)  
[Asanchem](https://www.linkedin.com/company/Asanchem)