

AKH-B 220

Wetting and Dispersing Additive (Solvent Based)

General wetting and dispersing additive for solvent-borne coatings for stabilizing fillers, organic, inorganic, and carbon black pigments in all kinds of resin systems (specially recommended for epoxy coatings) such as two-pack polyurethane and chlorinated polymer systems, two-pack epoxy resin systems, alkyd/amino resin combinations, nitrocellulose systems, solvent-based primer and base-coat of automotive coatings (saturated polyester systems).

Product Data

Physical Form:	Clear yellow liquid
Active Content:	50%
Non-volatile matter (10 min., 150 °C):	50%

Composition

Physical Form:	Clear yellow liquid
High molecular weight polyester	

Applications

Based on Total formulation weight:	0.2-0.5%
Titanium dioxide:	2%
Inorganic pigments:	3-5%
Organic pigments:	4-6%

Coatings > Solvent based systems
> Epoxy resin systems

Compatible with all resin types

**Applications >
Recommended for >
Particularly Recommended:**

Special Feature:



021-88864998
021-88865279
0912-5248514



www.asanchem.com



[@Asankimia](https://www.instagram.com/Asankimia)
[asan.chem](https://www.facebook.com/asan.chem)
[Asanchem](https://www.linkedin.com/company/Asanchem)